

#### Document 00.2 – Overview of the Metropolitan Water Reclamation District of Greater Chicago

Version Number: 3 Version Date: February 25, 2014

# **Description of the MWRDGC**

The Metropolitan Water Reclamation District of Greater Chicago (District) is an independent government and taxing body encompassing approximately 91% of the land area of Cook County, Illinois.

The District was originally organized as the Sanitary District of Chicago in 1889 under an act of the Illinois General Assembly. The enabling act in 1889 was in direct response to a typhoid and cholera epidemic which killed thousands of city residents. The District reversed the flow of the Chicago and Calumet River Systems to divert contaminated water from Lake Michigan, where it could be diluted as it flowed into the Des Plaines River and eventually the Mississippi River. Prior to the District's construction of a 61.3 mile system of canals and waterway improvements, the Chicago and Calumet River Systems were tributary to Lake Michigan. These river systems are now flow to the Illinois River system.

From 1955 through 1988, the District was called The Metropolitan Sanitary District of Greater Chicago (MSDGC or simply MSD). In order to provide a more accurate perception of the District's current functions and responsibilities, the name was changed effective, January 1, 1989, to Metropolitan Water Reclamation District of Greater Chicago (MWRDGC).

The District serves an area of 883.6 square miles which includes the City of Chicago and 125 suburban communities. The District serves an equivalent population of 10.35 million people; 5.25 million real people, a commercial and industrial equivalent of 4.5 million people, and a combined sewer overflow equivalent of 0.6 million people. The District's 554 miles of intercepting sewers and force mains range in size from 12 inches to 27 feet in diameter, and are fed by approximately 10,000 local sewer system connections. Local sewer systems are owned and operated by the individual communities and sewerage district.

The District's Tunnel and Reservoir Project (TARP) is one of the country's largest public works projects for pollution and flood control. Four tunnel systems total 109.4 miles of tunnels, 8 to 33 feet in diameter and 150 to 300 feet underground. One reservoir is in operation and construction is in progress on the remaining two.

The District owns and operates seven water reclamation plants (WRP) and 22 pumping stations. The District treats an average of 1.4 billion gallons of wastewater each day. The District's total wastewater treatment capacity is over 2.0 billion gallons per day.

The District controls approximately 76 miles of navigable waterways, which are part of a national system connecting the Atlantic Ocean and the Great Lakes with the Gulf of Mexico. In conjunction with its biosolids recycle and land reclamation program, the District owns over 13,500 acres of land in Fulton County, Illinois.





# **Description of District Facilities**

Hanover Park WRP	
Address:	1200 E. Sycamore
	Hanover Park, IL 60133
Distance:	35 miles northwest from the MOB, 45 minute drive
Employees:	23
Design Average Flow:	12 MGD
Plant Type:	Activated sludge
<b>Biosolids Production:</b>	1,000 DT/year

Solids Process	# of Units	Capacity/Dimensions
Gravity Belt Thickeners	2	250 gpm @ 3,125 lbs. dry solids/hr.
Anaerobic Digesters	6	40 ft Dia X 19.5 ft deep
Sludge Lagoons	2	450 ft long X 250 ft wide X 8.5 ft deep
Fischer Farm		183 acres (total) 127 acres (farm)

### John E. Egan WRP

Address:	550 S. Meacham Road
	Schaumburg, IL 60193
Distance:	30 miles northwest from the MOB, 40 minute drive
Employees:	42
Design Average Flow:	30 MGD
Plant Type:	Activated sludge
<b>Biosolids Production:</b>	7,500 DT/year

Solids Process	# of Units	Capacity/Dimensions
Gravity Belt	3	600 gpm
Thickeners	-	9F
Anaerobic	4	110 ft Dia X 34 ft deep
Digesters	4	
Centrifuges	3	25 DT/d, 300 hp motor

# James C. Kirie WRP

Address:	701 W. Oakton
	Des Plaines, IL 60018
Distance:	20 miles northwest from the MOB, 25 minute drive
Employees:	34
Design Average Flow:	52 MGD
Plant Type:	Activated sludge

Protecting Our Water Environment

Environmental Management System for Biosolids

Metropolitan Water Reclamation District of Greater Chicago

Biosolids Production: All waste activated sludge (WAS) is pumped to the Egan WRP for further processing.

Terrence J. O'Brien WR	
Address:	3500 W Howard Street
	Skokie, IL 60076
Distance:	15 miles north from the MOB, 25 minute drive
Employees:	156
Design Average Flow:	333 MGD
Plant Type:	Activated sludge
Biosolids Production:	All primary and WAS is pumped to the Stickney WRP for further
	processing.

### Stickney WRP

Address:	6001 W. Pershing Road
	Cicero, IL 60804
Distance:	12 miles southwest from the MOB, 20 minute drive
Employees:	397
Design Average Flow:	1,200 MGD
Plant Type:	Activated sludge
<b>Biosolids Production:</b>	120,000 DT/year

Solids Process	# of Units	Capacity/Dimensions
Sludge Concentration Tanks	16	70 ft long X 46 ft 9 in wide X 14 ft deep
Pre-Digestion Centrifuge	16	40 DT/d, 400 hp
Sludge Holding Tanks	12	70 ft long X 48 ft 1 inch wide X 11.5 ft water depth
Anaerobic Digesters	24	12 units @ 110 ft 12 units @ 120 ft water depth 33 ft water depth
Post Digestion Centrifuges:	18	40 DT/d, 300 hp motor



Calumet WRP	
Address:	400 E. 130th Street
	Chicago, IL 60628
Distance:	20 miles south from the MOB, 30 minute drive
Employees:	201
Design Average Flow:	354 MGD
<b>Biosolids Production:</b>	21,500 DT/year

Solids Process	# of Units	Capacity/Dimensions
Primary Sludge Concentration Tanks	2	100 ft long X 32 ft wide X 9.5 ft water depth
Sludge Concentration Tanks	12	60 ft Dia X 13 ft 9 in water depth
Anaerobic Digesters	12	110 ft Dia X 29 ft 10 in side water depth
Centrifuges	6	30 DT/d, 300 hp

### Lemont WRP

Address:	13 Stephen Street
	Lemont, IL 60439
Distance:	30 miles southwest from the MOB, 40 minute drive
Design Average Flow:	2.3 MGD
Employees:	4
<b>Biosolids Production:</b>	All primary and WAS is trucked to the Stickney WRP or Calumet WRP
	for further processing.

General Division Biosolic	ls Management Section 24	
Total Employees:	24	
Lawndale Avenue	e Solids Management Area (LASMA)	
Address:	7601 S. LaGrange Rd.	
	Willow Springs, IL 60480	
Distance:	25 miles southwest from the MOB, 35 minute drive	
	5 miles southwest from the Stickney WRP, 10 minute drive	
Biosolids:	LASMA receives biosolids from Stickney WRP and Egan WRP for further processing.	
Calumet Solids Management Area (CALSMA)		
Address:	Adjacent to the Calumet WRP	
Biosolids:	Receives biosolids from Calumet WRP for further processing.	



### Description of Solids Processes

#### Hanover Park WRP Solids Process

All solids produced at the Hanover Park WRP are anaerobically digested then dewatered in onsite lagoons. The biosolids are then applied via sub-surface injection at Fischer Farm, a District-owned site adjacent to the Hanover Park WRP as Class B biosolids.

#### John E. Egan WRP Solids Process

All solids produced at the John E. Egan WRP are anaerobically digested, and are:

- 1. Dewatered by centrifuging to approximately 25 percent solids content, and then:
  - a. Applied to land by a private contractor as a Class B cake.
    - b. Trucked to LASMA for further processing or distribution.
- 2. Pumped to the Terrence J. O'Brien WRP.

#### Stickney WRP Solids Process

All solids produced at the Stickney WRP are anaerobically digested and are then:

- 1. Placed into lagoons at LASMA for dewatering, aging, stabilization, and then transported to paved cell and air-dried prior to:
  - a. Application to land as Exceptional Quality (EQ) biosolids by a private contractor.
  - b. Application as EQ biosolids under the District's Controlled Solid Distribution Permit.
  - c. Use at local municipal solid waste landfills as final landfill cover.
  - d. Disposal in local municipal solid waste landfills.
- 2. Dewatered by centrifuging to approximately 25 percent solids content, and then applied to land by a private contractor as a Class B cake.
- 3. Dewatered by centrifuging to approximately 25 percent solids content, transported to paved cells at LASMA, and air-dried prior to use as daily landfill cover as Class B biosolids.
- Dewatered by centrifuging to approximately 25 percent solids content, placed into lagoons at LASMA for aging and stabilization, and transported to paved cells and airdried prior to:
  - a. Application to land as EQ biosolids by a private contractor.
  - b. Application as EQ biosolids under the District's Controlled Solid Distribution Permit.
  - c. Use at local municipal solid waste landfills as final landfill cover.
  - d. Disposal in local municipal solid waste landfills.
- 5. Dewatered to 25% total solids content by centrifuging and then conveyed to MBM's pelletizer facility where it is dried to approximately 95% total solids content. This product is then distributed to agricultural outlets and sod farms.

#### Calumet WRP Solids Process

All solids produced at the Calumet WRP are anaerobically digested and are then:

- 1. Placed into lagoons for dewatering, aging, stabilization, and then transported to paved cell and air-dried prior to:
  - a. Application to land as EQ biosolids by a private contractor.
  - b. Application as EQ biosolids under the District's Controlled Solid Distribution Permit.
  - c. Use at local municipal solid waste landfills as final landfill cover.
  - d. Disposal in local municipal solid waste landfills.

\\Falcon\M&O\Biosolids - EMS\Elements and Documents\Document 00.2 - Overview of the MWRDGC.doc Version Number: 3 Printed Versions of this document are unofficial. Official documents are located at <u>www.mwrd.org</u> Page 5 of 7

Protecting Our Water Environmen

- 2. Dewatered by centrifuging to approximately 25 percent solids content, and then applied to land by a private contractor as a Class B cake.
- 3. Dewatered by centrifuging to approximately 25 percent solids content, transported to paved cells, and air-dried prior to use as daily landfill cover as Class B biosolids.
- 4. Dewatered by centrifuging to approximately 25 percent solids content, placed into lagoons for aging and stabilization, and transported to paved cells and air-dried prior to:
  - a. Application to land as EQ biosolids by a private contractor.
  - b. Application as EQ biosolids under the District's Controlled Solid Distribution Permit.
  - c. Use at local municipal solid waste landfills as final landfill cover.
  - d. Disposal in local municipal solid waste landfills.

**Revision History** 

Version Number	Version Date	Description of Revision
0	7/28/05	Original issue.

\\Falcon\M&O\Biosolids - EMS\Elements and Documents\Document 00.2 - Overview of the MWRDGC.doc Version Number: 3 Printed Versions of this document are unofficial. Official documents are located at <u>www.mwrd.org</u> Page 6 of 7



# Environmental Management System for Biosolids

Metropolitan Water Reclamation District of Greater Chicago

1	3/19/10	Corrected the number of CWRP anaerobic digesters from 8 to 12. Added "Employees: 19" under LASMA. Added "(CALSMA)" after Calumet Solids Management Area. Added "Employees: 7" under CALSMA.
2	10/13/11	Edited Footer with Official Document Location
3	2/25/14	Updated data throughout to reflect 2014 Budget Book